



# 3216

## THERMALLY-BROKEN INSULATED STEEL SANDWICH DOOR

08 36 13/CHI  
Buyline 3132

The Door to Quality.

www.chiohd.com

C.H.I. OVERHEAD DOORS



9' x 7' 3216 white with optional 24" x 12" windows.

This model also available in



# DURABLE. THERMALLY-BROKEN.



## SPECIFICATIONS, OPTIONAL FEATURES AND ACCESSORIES



### END STILES

White painted end stiles are 4" or 8" wide to accommodate double or single-end hinges.



### SPRINGS

Torsion springs are helically wound with stress relieved, oil-tempered wire



### SECTION JOINT


Section joints are gasketed and thermally-broken for a tight weatherseal.

### OPTIONAL WINDOW DESIGNS


#### 24" SECTION HEIGHT




24" x 6"



24" x 12"



34" x 16"



FULL-VIEW



The Door to Quality.



COLOR SELECTION

Note: Refer to samples at your local C.H.I. distributor for exact color match.




Wind can be unpredictable and destructive. This is why C.H.I. Windbreaker Series and iSeries doors are designed, tested, and built to the most rugged specifications. Wind chamber tested to ensure wind-load resistance, these extra-sturdy designs provide enhanced defense against the elements.

C.H.I. Overhead Doors developed the resilient Windbreaker Series garage doors to protect against high wind conditions. The super-resilient C.H.I. iSeries Impact Approved doors have strength designed to withstand direct collision of projectiles and other windborne debris at high speeds.

### DOOR CONSTRUCTION

This Model utilizes 26-gauge exterior and 27-gauge interior steel skins injected with CFC free urethane insulation. The thermally-broken tongue and groove section joint includes a continuous weather seal offering exceptional protection from the elements.

Model 3216.....R-value\* - 17.54



## 26-GAUGE MODEL 3216, Thermally-Broken Insulated Steel Back

### SECTIONS

- Sections are 2" thick
- Sections include a thermal break to eliminate thermal convection
- Outside skin features horizontal micro-grooves
- Concealed steel back-up plates run from top to bottom of each section for secure hardware attachment
- Bottom "U" type astragal is a standard feature

### TRACKS

- Tracks are 2" or 3", as specified
- Available in bracket mount, angle mount, clip angle mount, 12" radius, 15" radius, high lift, vertical lift, roof pitch, or dual track low headroom

### HARDWARE

- Package includes 14 gauge or 11 gauge hinges, as specified
- 2" or 3" short-stem or long-stem ball bearing rollers
- Heavy duty adjustable top roller brackets

### SPRINGS

- Torsion springs are helically wound with stress relieved, oil-tempered wire
- Springs are individually calibrated per door
- Counter-balance torsion shafts are galvanized for rust resistance

### INSULATION TYPE

- Foamed in place CFC free polyurethane core
- R-value\* - 17.54

FEATURES

VISIT YOUR DOOR PROFESSIONAL AT:

C.H.I. Overhead Doors are manufactured in Arthur, Illinois, USA.



C.H.I. Overhead Doors is pleased to use DOW® insulation products in our urthane core garage doors.



\*R-value testing is in accordance with ASTM C518 standards.

All information presented is based on the specifications and features available at the time of printing and is subject to change without notice.