



Basic Reliability

AccessMaster® Garage Door Openers offer the added assurance of Security+ 2.0® Technology. Plus, each system includes several patented features designed to provide safety, security and reliability.

Connectivity

- MyQ® Technology enables you to securely monitor and control your garage door opener and houselights with your smartphone, tablet or computer. (Requires purchase of Internet Gateway (828LM).)
- Alerts can be received as email or pop-up (push) notifications on your mobile
 device so that you always know the status of your garage door and houselights.
- MyQ mobile app is a free download requiring no activation or subscription fee.

Performance

- 1/2 HP AC motor with industrial-strength chain drive provides steady performance and lifting power.
- Energy-efficient operation consumes up to 75% less power in standby mode.
- 4-year motor warranty and 1-year parts warranty.

Safety and Security

- Security+ 2.0 safeguards your household with every click a new code is sent to the garage door opener so that the door opens only for you.
- PosiLock® locks down your garage door by electronically monitoring against a forced opening.
- Alert-2-Close warning system provides audible and visual warnings when the garage door is about to close when using MyQ Technology.
- The Protector System® has safety sensors that project a light beam across the garage door opening, automatically reversing the door if anything interrupts the beam.

Included Accessories:



Security+ 2.0 Remote Control (891AC)

Allows you to control a single garage door opener, gate operator or MyQ Accessory. With Security+ 2.0, you are assured of a new code with every use.



Multi-Function Control Panel (882AC)

Allows you to program remote controls, keypads and MyQ Accessories from the control panel. Includes lockout remote controls for added security.

Optional Accessories:



3-Button Remote Control with Security+ 2.0 (893AC)

Allows you to control up to three garage door openers or gate operators or MyQ Accessories.



Internet Gateway (828LM)

Connect your MyQ-Enabled Garage Door Opener and Accessories to the Internet with this device.

SPEC SHEET

STANDARD SPECIFICATIONS

DIMENSIONS

Installed Length: 124"
Maximum Door Opening: 7' 6"*
Headroom Clearance Required: 2"
*Up to 10' with optional 8' or 10' rails

CARTONS

Number of Cartons: 2

Carton 1: Dimensions and Contents:

- 20" x 12" x 10"
- 882AC Door Control Panel
- 891AC 1-Button Remote Control
- Garage Door Opener Head
- The Protector System®

Carton 2: Dimensions and Contents:

- 10' 4" x 5" x 5"
- Assembled Solid-Steel T-Rail

SECURITY+ 2.0® RADIO CONTROLS

Coding System: Smart Receiver Code Button and Indicator Light

891AC 1-Button Remote Control Operating Range: 200' (approximately) Operating Temperature: -40°F to 150°F Battery (remote control): 3-Volt Lithium

Frequency:

- Remote Control: 310, 315, & 390 MHz Tri-Band

- Receiver: Frequency Agile on 310, 315, & 390 MHz

Security+ 2.0 Anti-Burglary Coding

CONVENIENCE / SAFETY

Maintenance Alert System

PosiLock®
Alert-2-Close
Emergency/Quick Release
Automatic Trolley Reconnect
Ventilation/Pet Opening
Down Safety Reverse
Up Safety Stop
Door Open/Beam Obstructed/Lights On
The Protector System®

ELECTRICAL SPECIFICATIONS

POWER

Voltage: 120V AC, 60Hz Current Rating: 6.0A UL Listings: Yes Length of Line Cord: 4' (3-prong)

ENERGY EFFICIENCY

Approximately 1 Watt Power in Standby Mode* *Standby Mode at down limit, work lights off

LOGIC TYPE

Solid-State Microcontroller with Built-in Surge Suppressor

LIGHTING

Number of Bulbs: 1 Maximum Wattage: 75

Length of Light Delay: 4 1/2 Minutes Type of Light Delay: Solid-State

MECHANICAL SPECIFICATIONS

MOTOR

M885: 1/2 HP RPM: 1625

Thermal protection: Automatic Lubrication: Permanent

DRIVE MECHANISM

Drive Means: Full Chain Reduction Means: Gear 16:1 Door Linkage: Adjustable Door Arm

ADJUSTMENT

Auto Force

Electronic Limit Settings

SHIPPING WEIGHT

M885: Head = 22 lbs. Rail/Full Chain: 20 lbs.

MATERIALS

Chassis: Steel Rail: Solid-Steel T Trolley: Steel

WARRANTY

4 Year Motor Warranty1 Year Parts Warranty

HOMELINK® Compatible (version 4.0 or higher) *

'May require an external adapter depending on the model and year of your vehicle. Visit homelink.com for additional information.

Note: To reduce the risk of injury to persons, when the Internet Gateway is used with garage door openers, the operator must be installed with sectional doors.